

NPR-2200-RT

Line interactive UPS Netys PR RT Rack/Tower 2200VA/1800W 230V AVR, 8 IEC sockets

The NETYS PR is the ideal solution for protecting small servers, networking devices and peripherals.

Strong points

- A secure and professional supply continuity
- Tailored to IT networking
- Simple to install
- Protection for your data line
- Meets practical needs
- Easy to use and to integrate

General characteristics

- 19" Rack & Rack/Tower convertible UPS.
- Sine Wave, AVR function (Automatic Voltage Regulation).
- Clear and uncluttered LCD interface.
- Wide range of communication protocols available in options.
- NTP data line suppressor.
- Up to 9 UPS output sockets.

Compliance with standards

- IEC/EN 62040-1, IEC/EN 62040-2
- AS 62040.1.1, AS 62040.1.2, AS 62040.2
- CE
- RCM (E2376)

Link to the reference



<https://apac.socomec.com/en/reference/NPR-2200-RT>

Classification

UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149

Commerce

Description	NeTYS PR-RT 2200VA/1800W 230V 50/60Hz WITH AVR, SINEWAVE,LCD PLUGSPROTECTEDRJ45,1xUSB,1xRS232 BATTERY INCLUDED
Effective date	2012-09-01
Offer Life Cycle Code	40
Country of origin	CN

ETIM - Electrical characteristics

Input voltage [V]	161..276
Primary frequency [Hz]	45..66
Number of phases primary	1
Output voltage [V]	230..230
Secondary frequency [Hz]	50..60
Output effective power [W]	1800
Output apparent power [VA]	2200
Number of phases secondary	1
SNMP	Yes
Voltage type	AC
Output power factor	0.8

ETIM - Mechanical characteristics

Height [mm]	87
Width [mm]	440
Depth [mm]	608
Weight [kg]	28.2
Construction type	Freestanding model
Input connection	C20
Number of output connections C13	8

ETIM - Technical features

USB interface	No
Bridging time full load [min]	11
Suitable for network-management	Yes
USV- technology	Line-interactive
Overall efficiency [%]	98
Efficiency in eco-mode [%]	98
Potential free switch contact	Yes
Auto shut down function	Yes

Logistics

GTIN/EAN	8027122515337
Customs number	8504409590
Price unit	PC

Weight of the packing unit [kg]	28.2
Length of the packing unit [m]	0.608
Width of the packing unit [m]	0.44
Depth of the packing unit [m]	0.087
Norms	
Conformity to standards	IEC
Technical Characteristics	
Height [mm]	87
Width [mm]	440
Depth [mm]	608
Weight [kg]	28.2
In/out	1/1
Output voltage	230
Rated frequency	50/50
Sn [kVA]	2.2
Pn [kW]	1.8
Conf	M2
Input voltage	230
Rate (min)	2.2
Rate (max)	2.2
Battery Life Time [Year]	03-05
Typical Backup Time [min]	9
Configuration	Line-Interactive UPS with AVR